



PRODUCT FEATURES


VENTRA RA is a combination of the multi louvred ventilator type VENTRA with a hinging base adaptor for roof access. This solution meets the need for a EN12101-2 certified natural smoke exhaust ventilator that is also suitable as a roof entry hatch. The base adaptor is formed from high quality corrosion resistant aluminium and is available with single wall or double wall insulated base. Sideways opening can be either manual with gas springs or with electric motors.

The VENTRA as opening lid is available with various louvre- and base options and has standard a 24 Vdc motor for daily ventilation and smoke exhaust.





Pol. Industrial Pinares Llanos, C/ Electricistas, 10 28670, Villaviciosa de Odón, Madrid - Spain //+34 916 162 695 //info@tria-spain.com www.tria-spain.com



TYPICAL APLICATIONS	To be installed on the roof, standard provided with a S5 flange type for fixing onto an upstand. Other flange options possible on request.
MATERIALS	Tempered aluminium, sea water and corrosion resistant (EN AW 5754). Corrosion resistant bearings. Built-in weather resistant hydrophobic tape. Note: aluminum is supplied untreated as standard. Possibility of being supplied with electrostatic painting (in any RAL color).
DIMENSIONS	Roof opening width: 900 – 1800 mm. Roof opening length: 966 – 2506 (11 louvres, max). Note: some configurations need to be evaluated due to louvres' materials. Please consult our technical department.
OPENING ANGLE	Ventra individual adjustable from 0° up to 90°. Access roof hatch opening up to 90°.
ROOF ACCESS	Manual roof access system, with latch.
CONTROLS	Operation VENTRA for day to day ventilation and smoke exhaust ventilation 24 Vdc electric, in accordance with EN 12101-02. Opening sideways for roof access manually with gas springs and handle with internal lock or 24 Vdc electric.




LOUVRES


AL	Single wall aluminium.
AL ISO	Double wall aluminium insulated.
PC16	Polycarbonate 16 mm, clear or opal

PC16Polycarbonate 16 mm, clear or opal.PC25Polycarbonate 25 mm, clear or opal.

BASES

Single aluminium Double wall aluminium with insulation.





DETAIL 01 single aluminium

DETAIL 02 double wall aluminium with insulation

FLANGES

Hinging base

Note: custom flange design and insulated flanges upon request.



S5

WEIGHT


Depends on dimensions and type of infill


OPTIONS

Polyester powder coating










//0

ПЙ

SECTION S2






FRONT VIEW






•••




SIDE VIEW


SECTION S1







VENTRA RA - CLOSED PERSPECTIVE



VENTRA RA - OPEN PERSPECTIVE

